

HD TVI TURRET CAMERA

720P IR Outdoor Turret Camera



The 0E-HDDF720P is a 1.0 MP (1280 X 720) turret camera constructed with a 2.8mm lens. This 1.0 MP Camera is IP66 rated and provides HD Image quality and is ideal for numerous indoor/outdoor applications such as commercial applications, home or office use as well as monitoring hallways, unattended storage areas and various other installation applications.

- 2.8 mm lens
- IR up to 20M (65 ft)
- 1280 X 720 Picture Quality
- 24 IR LEDs
- TVI + CVBS Dual Output
- True Day Night
- Operating Temperature -40 °C – 60 °C (-40 °F – 140 °F)
- Max. 4W Power Consumption
- IP 66 Rated
- 12V DC
- 3 Year Warranty

PART #: 0E-HDDF720P

UPC: 811914025740

LENGTH: 2.75"

WIDTH: 3.52"

HEIGHT: 3.52"

WEIGHT: 9.17 ounces



Specifications

Model	0E-HDB720P	0E-HDDF720P	0E-HDD28W
Camera			
Image Sensor	1MP CMOS Image Sensor	1MP CMOS Image Sensor	2MP CMOS Image Sensor
Effective Pixels	1296(H)*732(V)	1296(H)*732(V)	1928(H)*1088(V)
Min. Illumination	0.1Lux @ (F1.2, AGC ON) ,0 Lux with IR	0.1Lux @ (F1.2, AGC ON) ,0 Lux with IR	0.01Lux @ (F1.2, AGC ON) ,0 Lux with IR
Shutter Time	1/30 s to 1/50,000 s		
Lens	3.6mm	2.8mm	
	Angle of view: 70.9°	Angle of view: 92°	Angle of view: 103°
Angle Adjustment	Pan: 0 - 360°, Tilt: 0 - 180°, Rotation: 0 - 360°	Pan: 0 - 360°, Tilt: 0 - 75°, Rotation: 0 - 360°	
Day &Night	ICR		
Digital Noise Reduction	Yes		
HD Video Output	1 Analog HD output		
Video Frame Rate	1280 × 720@30fps	1280 × 720@30fps	1920 × 1080@30fps
Menu	/		White Balance, BLC, AGC, D/N Mode Function:Wide Dynamic Range; Digital Noise r eduction; Mirror; SMART IR
General			
Operating Conditions	-40° C – 60° C (-40° F – 140° F); Humidity 90% or less (non-condensing)		
Power Supply	12 VDC ± 15%		
Power Consumption	Max. 4 W		Max. 5 W
Ingress Protection level	IP66		
IR Range	Up to 20m		
Dimensions	Φ70×149.5 mm (Φ2.76″ ×5.89″)	Φ89.5 × 69.8 mm(Φ3.52″ × 2.75″)	91mm×82.6mm×68.3mm (3.58"×3.25"×2.69")
Weight	360g (0.79lb)	260g (0.57lb)	350g (0.77lb)